

SYNTEKO RETARDER

1670



A mixture of solvents to be added to Synteko CLASSIC to delay the solvent evaporation and thereby maintain a reasonable drying time, also at high temperatures.

USAGE AREA:

to be added to Synteko CLASSIC

TECHNICAL DATA:

Base material	Solvent mixture
Solvent	Ethanol and aliphatic diester
Density	Approx. 900 kg/m ³ (8,68 lb/gal US) (10,42 lb/gal UK)
Fire hazards	Highly flammable 14°C (57°F)
Storage	Not sensitive to freezing
Self life	24 months in unopened container from production date (s. package)
Package size	1L

DIRECTION FOR USE

Synteko CLASSIC 1636, 1637 and 1646 can be diluted max. 5 % with Synteko RETARDER. Add Synteko RETARDER to the finish and mix well before adding the Synteko Hardener 1647. Synteko RETARDER must be used in the last coat only.

HEALTH & SAFETY INFORMATION

FOR PROFESSIONAL USE ONLY! Detailed information and guidance is provided in our MSDS (Material Safety Data Sheet) www.synteko.com. The following only represents a selection of important information.



Danger! Highly flammable liquid and vapour. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed. Do not get in eyes, on skin, or on clothing. Call a POISON CENTER or doctor/physician if you feel unwell. Keep cool. Dispose of contents and container in accordance with all local, regional, national or international regulations. Hazardous ingredients: acetone. Repeated exposure may cause skin dryness and cracking.

Our information is based on laboratory tests and is considered a guide in connection with choice of product and working method. As your working conditions are beyond our control, we do not assume any responsibility for the results. Our responsibility covers exclusively personal injury and damage to property, which actually have been proved subsequent to faults and defects in one of the products manufactured by us.

Producer:
Sika Estonia OÜ, Estonia
www.synteko.com

Date: 29.07.2014